

# Bodyguard 323 classic

## Multi Therapy Infusion Pump



## features

- ✔ **Supports Multiple Languages**  
Over 20 languages available to meet your needs and preferences.
- ✔ **Inpatient/Outpatient Accessories**  
A docking station and lockbox are available for pole-mounted use, and a carrying pouch for home care.
- ✔ **Rechargeable or Disposable Batteries**  
Choose a rechargeable Li-Polymer battery or a standard 9V (x2) disposable battery pack.
- ✔ **Money-Saving Rechargeable Battery**  
A recent cost analysis estimates a savings of € 500.00 per pump per year using the rechargeable battery.
- ✔ **Uses Standard Medication Bags**  
Reduce your cost of disposables.
- ✔ **Post-Occlusion Bolus Reduction System**  
Prevents delivery of false boluses following a downstream occlusion event.
- ✔ **Precise In-Line Pressure Detection**  
Detects downstream and upstream pressure; graphically displayed on screen.
- ✔ **Auto Bolus Rate Reduction**  
Overcome patient back pressure to help prevent transient occlusion alarms.
- ✔ **Built-in Free Flow Protection**  
CME administration sets include an integrated anti-siphon valve to meet JCAHO guidelines.
- ✔ **3-Level Access Codes**  
Prevent accidental or unauthorized program changes.

## overview

Deliver the widest range of care you'll find in one infusion pump. Programmable for antibiotics, chemotherapy, TPN and PCA, the BodyGuard 323™ pump equips you with many therapeutic options. The compact, competitively-priced BodyGuard 323™ pump fits wherever you deliver care. Use it pole-mounted at bedside or at a home environment. Clinichain can advise this pump for the following applications:

Critical care, Patient transport, Emergency medicine, Fluid replacements, Lipids, Enzyme replacements, Chronic pain management

## techspecs

### Delivery Modes

Continuous, 25-Steps, TPN, Intermittent & PCA

### Delivery Routes

Parenteral, Intravenous, Subcutaneous, Percutaneous, Intra-Arterial

### Concentration Units

mg/mcg

### Flow Rate Range & Accuracy

0.1-99.9 ml/h; 0.1ml/h Steps

### Primary & Piggy (Secondary)

100-1200 ml/h; 1ml/h Step

### Flow Rate Accuracy

± 5 %

### Dimensions; pump only (HxWxD)

112 x 89 x 40 mm

### Weight (with standard battery)

390g

