## **INCUBATORS**

# Incubator 10L, 23L, 56L



#### features

- Digital Bench Top Incubators
- Door with large window
- Precise temperature control by hydraulic thermostat
- Ideal for microbiology or hematology applications
- Corrosion resistant chamber
- Three shelf levels
- PID regulation with PT100 temperature sensor
- C LED display
- Digital version is not available in Europe and Swiss.
- - 10l 2 positions, 1 shelf included
  - 23I 3 positions, 2 shelves included
  - 56l 5 positions, 2 shelves included



#### overview

Digital incubators are compact and economically priced, yet offers features not typically found in a basic incubator.

The housing is all metal, as is the door frame. See-through acrylic door lets you view contents without opening the door. Included shelves can be adjusted to different levels.

The heating elements in the incubator are incorporated into the bottom and sides of the aluminum chamber. This provides better temperature stability and uniformity than other incubators in it's class. A grommet hole in the top of the unit can hold a thermometer for accurate temperature setting.

### techspecs

Temperature range

Ambient +5°C to +70°C

Stability

±0,5°C at 37°C

Power source

230 V / 50-60 Hz

10L - 70VA, 23L - 160VA, 56L - 220VA

Capacity

10 or 20 or 56 liters

Dimensions (W x D x H)

10I - 285 x 280 x 335mm

23I - 340 x 360 x 400mm

56I - 453 x 420 x 546mm

Weight

10L -8.3 kg, 23L - 12,8 Kg, 56L - 23,6 Kg

